





# HSF

NOTES:  
 Rated Current:0.75AMP.  
 Contact Resistance:30mΩ Max.  
 Withstand Voltage:500V AC/DC  
 Insulation Resistance:1000MΩ Min.  
 Operation Temperature:-40°C to +105°C

Contact Material:Brass  
 Contact Plating:Au Over Ni  
 Insulator Material:PA9T+33%G.F UL94V-0 BK

Recommended P.C.B Layout (Top Side)  
 (PCB BOARD TOLERANCE±0.05)



## Ordering Information

### 1515-12 XX XX R 070 C A XX

No. of Pins Contact Plating Pin Length(Short) Insulator Packing Series No.  
 Per Row:01~50 G0=Gold Flash L=A+B+D+2.6 C=PA9T A=Tray 01~99  
 G3=10u"Gold Standard:070=7.0  
 G4=15u"Gold  
 G5=30u"Gold  
 SN=Tin  
 SM=Matte Tin

Item	Pin Length	A	E	B
Standard	7.0	1.80	2.50	1.80
Alternate				

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
A2	2018/01/05	MODIFY PART NO.	-----	X.X ±0.40	William Chen	2018/01/05	UNIT	mm [inch]	1515-12XXXXRXXCX XX
A1	2012/11/20	Modify the material	-----	X.XX ±0.25	CHECK	DATE	SIZE	A4	TITLE: 1.00 Pin Header, DUAL ROW, R/A, H=1.5
A0	2012/03/01	NEW	-----	X.XXX ±0.15	APPROVE	DATE	SHEET	1/1	Customer NO.
				Angle ± 3'			PROJ.		
				DIM TOL					

**WCON**  
 Http: www.wcon.com  
 WCON-Dongguan Tel: +86 769 85358920  
 WCON-Kunshan Tel: +86 512 57468408  
 Fax: +86 769 85358915  
 Fax: +86 512 57468468  
 E-mail: sales@wcon.com  
 E-mail: salesks@wcon.com